BZ 30T/12-2
BZ 50T/12-2
BZ 50T/25-2

High Frequency Welding-Blanking Machine

BIZETA S.r.l.
Via Bragni, 93/A
35010 Cadoneghe (PD) Italy
Tel: +39 0499220298 FAX: +39 0499220298
E-mail: commerciale@bizeta-macchinehf.it
www.bizeta-macchinehf.it

BZ 50T/25-2 - Technical Features

Feature	Unit	Value
Maximum welding force	kg	50,000
Maximum blanking force	kg	60,000 (52,000 with cylinder)
Maximum high-frequency power at electrodes	kW	30
Nominal operating frequency	MHz	27.12
Electrode-holder plate dimensions	mm	800 x 500
Maximum clearance between working table and electrode-holder plate	mm	115
Maximum stroke of electrode-holder plate	mm	100
Maximum absorbed power	kW	42
Supply voltage	V	3x400+T
Maximum production rate	No.	400 strokes/hour
Overall machine dimensions	mm	4,800 x 2,700 x 2,300 h
Approximate net weight	kg	6,840
Automatic movable working tables	No.	2

The above-mentioned aesthetic and technical specifications are not binding. Our company reserves the right to introduce, without prior notice, any modifications to improve the performance and operation of the machine.